



## Test Report

No.: GZHL1811049924HM

Date: Nov 21, 2018

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : HRO-121 MOTOR HELMET  
Style / Item No. : HRO-121  
Size : M(57-58cm); L(59-60cm);XL(61-62cm)  
HPI (from basic plane) : M: 50mm for C-dot  
L: 55mm for C-dot  
XL: 60mm for D-dot  
Buyer :  
Test Performed : Selected test(s) as requested by applicant  
Sample Receiving Date : Nov 15, 2018  
Test Performing Date : Nov 15, 2018 to Nov 21, 2018  
Test Result(s) : For further details, please refer to the following page(s)

Signed for and on behalf of  
Guangzhou Branch  
SGS-CSTC Ltd.

Arthur Mak  
Approved Signatory



GZHL1811049924HM



SGS-CSTC Inspection & Testing Services Co., Ltd.  
Guangzhou Branch Testing Center H14010105

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

198 Kezhu Road, Sciencetech Park Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075191 [www.sgs.com](http://www.sgs.com)  
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075191 e [sgs.china@sgs.com](mailto:sgs.china@sgs.com)

**Test Conducted: Based on 49 CFR CH.V (10-1-15 EDITION) PART 571-FMVSS § 571.218 Motorcycle Helmets**

**Number of Tested Sample: \_12\_ piece(s)**

**Test Results: Details shown as following table**

Clause	Test Method/Requirement	Test Result
<b>5</b>	<b>Requirements</b> Each helmet shall meet the requirements of S5.1, S5.2, and S5.3 when subjected to any conditioning procedure specified in S6.4, and tested in accordance with S7.1, S7.2, and S7.3	
<b>5.1</b>	<b>Impact attenuation</b> When an impact attenuation test is conducted in accordance with S7.1, all of the following requirements shall be met: (a) Peak accelerations shall not exceed 400g; (b) Accelerations in excess of 200g shall not exceed a cumulative duration of 2.0 milliseconds; and (c) Accelerations in excess of 150g shall not exceed a cumulative duration of 4.0 milliseconds.	Pass See annex 1
<b>5.2</b>	<b>Penetration</b> When a penetration test is conducted in accordance with S7.2, the striker shall not contact the surface of the test headform.	Pass See annex 4
<b>5.3</b>	<b>Retention system</b>	
<b>5.3.1</b>	When tested in accordance with S7.3: (a) The retention system or its components shall attain the loads specified without separation; and (b) The adjustable portion of the retention system test device shall not move more than 1 inch (2.5 cm) measured between preliminary and test load positions.	Pass See annex 2
<b>5.3.2</b>	Where the retention system consists of components which can be independently fastened without securing the complete assembly, each such component shall independently meet the requirements of S5.3.1	NA
<b>5.4</b>	<b>Configuration</b> Each helmet shall have a protective surface of continuous contour at all points on or above the test line described in S6.2.3. The helmet shall provide peripheral vision clearance of at least 105° to each side of the mid-sagittal plane, when the helmet is adjusted as specified in S6.3. The vertex of these angles, shown in Figure 3, shall be at the point on the anterior surface of the reference headform at the intersection of the mid-sagittal and basic planes. The brow opening of the helmet shall be at least 1 inch (2.5 cm) above all points in the basic plane that are within the angles of peripheral vision	Pass See annex 3



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

<p><b>5.5</b></p>	<p><b>Projections</b> A helmet shall not have any rigid projections inside its shell. Rigid projections outside any helmet's shell shall be limited to those required for operation of essential accessories, and shall not protrude more than 0.20 inch (5 mm).</p>	<p>Pass</p>
<p><b>5.6</b></p>	<p><b>Labeling</b></p>	
<p><b>5.6.1</b></p>	<p>Each helmet shall be labeled permanently and legibly, in a manner such that the label(s) can be read easily without removing padding or any other permanent part, with the following:</p>	<p>Pass</p>
	<p>(a) Manufacturer's name.</p>	<p>Pass</p>
	<p>(b) Discrete size.</p>	<p>Pass</p>
	<p>(c) Month and year of manufacture. This may be spelled out (for example, June 2010), or expressed in numerals (for example, 6/10).</p>	<p>Pass</p>
	<p>(d) Instructions to the purchaser as follows:</p>	<p>Pass</p>
	<p>(1) "Shell and liner constructed of (identify type(s) of materials)</p>	<p>Pass</p>
	<p>(2) "Helmet can be seriously damaged by some common substances without damage being visible to the user. Apply only the following: (Recommended cleaning agents, paints, adhesives, etc., as appropriate)</p>	<p>Pass</p>
	<p>(3) "Make no modifications. Fasten helmet securely. If helmet experiences a severe blow, return it to the manufacturer for inspection, or destroy it and replace it."</p>	<p>Pass</p>
	<p>(4) Any additional relevant safety information should be applied at the time of purchase by means of an attached tag, brochure, or other suitable means</p>	<p>Pass</p>
	<p><b>Certification</b></p>	
	<p>Each helmet shall be labeled permanently and legibly with a label, constituting the manufacturer's certification that the helmet conforms to the applicable Federal motor vehicle safety standards, that is separate from the label(s) used to comply with S5.6.1, and complies with paragraphs (a) through (c) of this section.</p>	<p>Pass</p>
	<p>(a) Content, format, and appearance. The label required by paragraph S5.6.2 shall have the following content, format, and appearance:</p>	<p>Pass</p>
	<p>(1) The symbol "DOT," horizontally centered on the label, in letters not less than 0.38 inch (1.0 cm) high.</p>	<p>Pass</p>
	<p>(2) The term "FMVSS No. 218," horizontally centered beneath the symbol DOT, in letters not less than 0.09 inches (0.23 cm) high.</p>	<p>Pass</p>
	<p>(3) The word "CERTIFIED," horizontally centered beneath the term "FMVSS No. 218," in letters not less than 0.09 inches (0.23 cm) high.</p>	<p>Pass</p>
	<p>(4) The precise model designation, horizontally centered above the symbol DOT, in letters and/or numerals not less than 0.09 inch (0.23 cm) high.</p>	<p>Pass</p>
	<p>(5) The manufacturer's name and/or brand, horizontally centered above the model designation, in letters and/or numerals not less than 0.09 inch (0.23 cm) high.</p>	<p>Pass</p>
	<p>(6) All symbols, letters and numerals shall be in a color that contrasts with the background of the label.</p>	<p>Pass</p>
	<p>(b) Other information. No information, other than the information specified in subparagraph (a), shall appear on the label.</p>	<p>Pass</p>

